

**PSX Series Buffer (Heating) Tank**



RST 37-2 steel buffer tank for heating systems

- 90 mm foam insulation
- Removable insulation jacket
- 5 x 1 ½” tapping points



<b>Technical Data:</b>	<b>PSX 500</b>	<b>PSX 600</b>	<b>PSX 800</b>	<b>PSX 1000S</b>	<b>PSX 1500</b>	<b>PSX 2000</b>
Height	1942 mm	1626 mm	1966 mm	2010 mm	2246 mm	2413 mm
Ø with insulation	830 mm	930 mm	930 mm	1030 mm	1170 mm	1280 mm
Ø without insulation	650 mm	750 mm	750 mm	850 mm	990 mm	1100 mm
Weight	117 kg	125 kg	135 kg	158 kg	262 kg	448 kg
Heating connections	1½”	1½”	1½”	1½”	1½”	1½”
Sensor pockets	√	√	√	√	√	√
Max. operating pressure	3 bar	3 bar	3 bar	3 bar	3 bar	3 bar
Max. temperature	95 <sup>o</sup>	95 <sup>o</sup>	95 <sup>o</sup>	95 <sup>o</sup>	95 <sup>o</sup>	95 <sup>o</sup>

Buffer tanks can be custom designed with additional tapping points, flange and/or heat exchangers.